

FASTLIFT DROP-FORGED EYEBOLTS

to DIN 580
(Galvanised)



Thread diameter mm	Safe working load at 0° kg	Inside eye diameter mm	Eye material diameter mm	Shank length mm	Thread length mm	Approx weight kg
6	70	15	6	11	9	0,05
8	140	19	8	12	9	0,06
10	230	24	10	16	13	0,11
12	340	29	11	20	17	0,18
14	490	34	14	26	22	0,28
16	700	34	14	27	22	0,32
18	850	40	16	29	25	0,35
20	1200	39	16	30	25	0,45
22	1500	44	19	32	28	0,63
24	1800	49	20	36	30	0,76
30	3600	59	25	46	38	1,88
33	4300	59	25	46	38	2,16
36	5100	70	27	60	51	2,92
42	7000	80	31	65	58	4,03
48	8600	90	40	70	60	6,38
56	11500	109	47	83	70	8,80
64	16000	109	47	90	75	12,40

FASTLIFT DROP-FORGED EYENUTS

to DIN 582
(Galvanised)



Thread diameter mm	Safe working load at 0° kg	Inside eye diameter mm	Eye material diameter mm	Base diameter mm	Thread length mm	Approx weight kg
6	70	19	8	20	10	0,05
8	140	19	8	20	10	0,05
10	230	24	10	25	12	0,09
12	340	29	11	29	13	0,16
14	490	34	14	34	14	0,24
16	700	34	14	34	16	0,24
18	850	39	18	41	20	0,30
20	1200	39	16	40	19	0,36
22	1500	44	18	45	19	0,55
24	1800	49	20	51	23	0,67
30	3600	59	25	67	27	1,32
33	4300	59	26	67	27	1,88
36	5100	70	30	75	32	2,08
42	7000	80	30	86	39	3,20
48	8600	90	38	96	51	5,00
56	11500	109	46	112	58	6,95
64	16000	109	46	112	58	9,80



STAINLESS STEEL EYEBOLTS AND EYENUTS

AVAILABLE IN

6, 8, 10, 12, 14, 16, 20, 22 AND 24mm THREAD SIZES

