

FASTLIFT DROP-FORGED EYEBOLTS

to British Standard Specifications
(Ungalvanised)



WITH METRIC THREADS TO BSS 4278 TABLE 1

Thread diameter mm	Safe working load at 0° kg	Inside eye diameter mm	Eye material diameter mm	Shank length mm	Thread length mm	Approx weight kg
6	60	15	9	21	17	0,07
8	150	14	9	18	13	0,08
10	330	15	9	19	15	0,08
12	400	15	9	19	15	0,09
14	500	20	12	22	17	0,22
16	800	20	12	22	17	0,23
18	1200	24	15	29	24	0,34
20	1600	27	16	31	24	0,45
22	1600	28	16	32	24	0,54
24	2500	35	21	40	34	0,91
27	2500	37	22	44	37	1,64
30	4000	43	26	50	40	1,71
33	4000	44	28	52	44	2,88
36	6300	54	32	65	57	3,29
39	6300	55	34	70	60	5,04
42	8000	60	36	75	64	6,24
45	8000	65	40	80	68	7,16
48	10000	65	40	80	68	7,60
52	12500	73	48	88	75	10,18
56	16000	82	51	108	93	15,22
64	20000	90	57	115	100	19,50
72	25000	113	68	137	110	30
76	25000	115	68	137	110	30

WITH BSW THREADS TO BSS 529 PART 1

Thread diameter ins	Safe working load at 0° kg	Inside eye diameter mm	Eye material diameter mm	Shank length mm	Thread length mm	Approx weight kg
3/8	250	14	9	17	14	0,06
1/2	500	19	11	25	20	0,12
5/8	900	24	14	30	23	0,25
3/4	1400	28	17	34	27	0,45
7/8	2000	33	20	41	31	0,63
1	2750	38	22	44	36	1,05
1-1/8	3500	44	26	53	46	1,60
1-1/4	4500	47	30	59	49	3,14
1-1/2	6500	54	34	70	59	4,56
1-3/4	9000	66	39	82	68	5,60
2	12000	72	47	93	78	9,10
2-1/4	15000	82	54	100	88	15,00
2-1/2	20000	92	58	112	98	17,70

BRITISH STANDARD EYEBOLTS MAY BE USED TO LIFT INCLINED LOADS. THE SAFE WORKING LOAD PER EYEBOLT WILL BE REDUCED BY APPROXIMATELY 65% FOR ANGLES OF 30° AND APPROXIMATELY 75% FOR ANGLES OF 45%.