

FASTLIFT RIGGING SCREWS

DROP-FORGED CLOSED BODY WITH LOCK-NUTS



OVAL EYE AND EYE



OVAL EYE AND JAW



JAW AND JAW

Thread diameter mm*	Body length mm	Approx. take-up mm	Eye inside length mm	Eye inside width mm	Jaw inside length mm	Jaw inside width mm	Eye material diameter mm	Jaw pin diameter mm	Overall closed length mm	Overall open length mm	Safe working load kg	Approx. weight kg
10	123	80	13	13	21	10	8	8	235	315	500	0,28
12	193	130	29	14	25	12	11	10	330	462	700	0,66
16	230	140	40	16	32	17	15	10	410	550	1200	1,20
20	230	140	50	21	37	19	17	16	440	580	1500	2,15
22	295	215	50	23	43	24	17	20	535	750	2200	3,30
24	350	240	55	24	52	28	17	22	610	850	3200	5,20
32	370	260	64	30	62	31	20	26	700	960	4800	9,35
38	410	280	64	35	70	36	22	32	740	1020	6000	11,20
51	420	310	100	44	100	53	38	39	800	1110	11000	22,00

*Please note: threads may be Imperial size. Metric equivalents stated for convenience.

DROP-FORGED EXTRA-LONG OPEN BODY



JAW AND JAW

AVAILABLE IN 6, 8, 10, 12, 16, 20 and 24 mm THREAD SIZES

STAINLESS STEEL



JAW AND JAW

AVAILABLE IN 6, 8, 10, 12 and 16 mm THREAD SIZES