

# FASTLIFT TURNBUCKLES

DROP-FORGED TO DIN 1480



EYE AND EYE



HOOK AND EYE



HOOK AND HOOK

Thread diameter mm	Body length mm	Approx. take-up mm	Eye inside diameter mm	Hook throat opening mm	Overall closed length mm	Overall open length mm	Safe working load kg	Approx. weight kg
6	110	85	8	8	170	250	220	0,10
8	110	80	10	10	180	260	410	0,17
10	125	85	12	12	210	300	660	0,29
12	125	80	17	15	225	320	940	0,45
14	140	92	17	18	265	355	1320	0,61
16	170	115	19	20	305	420	1800	0,95
20	200	130	24	22	360	480	2750	1,85
22	220	145	28	24	400	545	3300	2,20
24	250	170	28	28	440	610	4000	3,15
30	250	170	30	29	480	640	6620	5,25
36	290	180	48	29	550	720	9280	8,00
42	330	205	48	46	675	870	13200	13,00
48	350	200	55	55	730	900	16800	25,00

## DROP-FORGED TO DIN 1480 WITH WELDABLE ENDS



AVAILABLE IN 6, 8, 10, 12, 14, 16, 20, 22, 24, 30 and 36 mm THREAD SIZES

## DIE CAST

EYE AND EYE

HOOK AND EYE

HOOK AND HOOK

Thread diameter mm	Body length mm	Approx. take-up mm	Eye inside diameter mm	Hook throat opening mm	Overall closed length mm	Overall open length mm	Approx. weight kg
4	45	34	7	7	83	117	0,03
5	70	50	8	7	110	160	0,04
6	100	70	10	8	156	226	0,07
8	110	80	11	9	180	260	0,15
10	120	89	16	13	204	293	0,25
12	130	89	18	17	240	329	0,36

## STAINLESS STEEL

EYE AND EYE

HOOK AND EYE

HOOK AND HOOK

AVAILABLE IN 5, 6, 8, 10, 12 and 16 mm THREAD SIZES